


Standby Series  
**CP425SLG**



**MSRP:** \$44.95

- 425VA/225Watts
- 8 Outlets
- Compact form
- Widely-spaced outlets
- RJ11/USB ports
- EMI/RFI filters

The CyberPower Standby CP425SLG uninterruptible power supply (UPS) safeguards a home office PC and other electronics (monitors, printers, scanners, speakers, fax machines, CD/DVD players and iPods) from surges, spikes, sags, brownouts and other power abnormalities. Its composite integrated circuitry offers advanced lightning protection. Patented GreenPower UPS™ advanced circuitry reduces UPS energy costs by up to 75% compared to competitive models.

The CP425SLG unit has a capacity of 425VA/225Watts, eight (8) NEMA 5-15R receptacles, widely-spaced to accommodate transformer-based plugs. Its compact design allows for horizontal or vertical placement, or it can be conveniently mounted on a wall. This UPS has a maintenance-free, user-replaceable 12V/3.6Ah battery and offers connectivity via one (1) HID USB port and a serial-to-USB cable. Protection for phone/network (RJ11) is also included. EMI/RFI filters increase the immunity of the load to disturbances and surges. PowerPanel® Personal Edition UPS Management software is included to monitor the vitals of the UPS and will safely shutdown the system in case of a power outage.

A Three-Year Warranty ensures that this UPS has passed our highest quality standards in design, assembly, material or workmanship and further protection is offered by a \$75,000 Connected Equipment Guarantee.

<b>Runtimes</b>	<b>Half-Load (minutes)</b>	<b>Full-Load (minutes)</b>
CP425SLG	7	2

**Energy-Saving Technology** - Patented GreenPower UPS™ advanced circuitry reduces UPS energy costs by up to 75% compared to competitive models. Ultra-Quiet Operation - Lowest

sound emissions of any UPS in its class. EMI/RFI Filters - Shielding against electromagnetic interference and radio frequency signals prevents line noise ("humming") over telephone lines or audio systems. Transformer-Spaced Outlets - Widely-spaced outlets accommodate large transformer-based plugs without compromising the utility of other outlets. USB Connectivity - HID compliant USB port enables full integration with built-in power management and auto shutdown features of Windows, Linux and Mac OS X. Convenient Mounting - Multiple mounting options: horizontal, vertical, cabinet, and wall. LED Indicators - LED status lights indicate Power-On and wiring faults. Audible Alarms - Distinctive tones identify when the unit is running on battery power, if it is overloaded or when the battery is low. Resettable Circuit Breaker - The user may use this convenient unit reset switch in case of an overload. PowerPanel® Personal Edition UPS Management Software - In event of a power outage, PowerPanel saves open files and "hibernates" the PC to increase the run-time on the UPS unit. PowerPanel is easily installed on any Windows-based PC and uses minimal system resources. Diagnostic screens display the status of the UPS, including silent operation mode, configurable system notifications, automatic self tests, adjustable high/low voltage warnings, event/data logging, and scheduled shutdowns. 3-Year Warranty - Stringent manufacturing processes and innovative product design enables CyberPower to offer one of the strongest warranties in our industry. CyberPower will replace damaged units within three (3) years of purchase date. #1 Rated Technical Support Team - CyberPower assists users with any product, installation, or warranty concerns - free of charge! ISO and Safety Certifications - All CyberPower manufacturing facilities are state-of-the-art and ISO-9001 Quality Tested. Our products are certified by the FCC, cUL, and UL. Windows Compatibility - Our PowerPanel® power management software has been fully tested and is compatible with Windows 2000, 2003, XP 32/64, Vista 32/64, 7, and Server 2008.

**General**

UPS Topology	Standby
Energy Saving	Yes - GreenPower UPS™ High Efficiency

**Input**

Voltage	96Vac - 140Vac
Frequency	47Hz - 63Hz
Plug Type	NEMA 5-15P
Plug Style	Right angle, 45 degree offset to the right
Cord Length	5'
Circuit Breaker	10 Amp

**Output**

VA	425
Watts	255

On Battery Voltage	120Vac +/- 7%
On Battery Frequency	50/60Hz +/- 1%
On Battery Waveform	Simulated sine wave
Overload Protection	Internal circuitry limiting / circuit breaker
Outlets - Total	8
Outlet Type	NEMA 5-15R
Outlets - Battery & Surge Protected	4
Outlets - Surge-Only Protected	4
Outlets - Widely Spaced	4
Transfer Time	4ms
<b>Battery</b>	
Runtime at Half Load (min)	7
Runtime at Full Load (min)	2
Battery Type	Sealed lead acid
Battery Size	12V/3.6AH
User Replaceable	No
Typical Recharge Time	8 Hours
Replacement Battery	BB Battery - BP3.6-12
Battery Quantity	1
<b>Surge Protection and Filtering</b>	
Surge Suppression	890 Joules
Phone Protection RJ11	1-In, 2-Out
EMI/RFI Filtration	Yes
<b>Management &amp; Communications</b>	
HID Compliant USB Port	Yes
Serial Port	No
Management Cable	
LED Indicators	Power on, wiring fault
Audible Alarms	On battery, low battery, overload
Software	PowerPanel Personal Edition
<b>Physical</b>	
Form Factor	Compact
Dimensions (WxHxD)	9.75" x 6" x 3"
Weight (lbs)	5
Keyhole Mounting Slots	Yes
<b>Environmental</b>	
Operating Temperature	32 °F to 95°F / 0°C to 35 °C
Operating Humidity	0% - 90% non condensing
<b>Certifications</b>	

Certifications	UL1778, cUL 107.3, FCC DOC Class B
ROHS	ROHS Compliant
<b>Warranty</b>	
Product Warranty	3 Years Limited
Connected Equipment Guarantee	Lifetime
CEG Amount	\$75,000