

# Specifications

## SCX-5635FN

<b>Print</b>	
Speed (Mono)	Up to 33 ppm in A4 (35 ppm in Letter)
Resolution	Up to 1200 x 1200 dpi effective output
First Print Out Time (Mono)	Less than 8 seconds
Emulation	PCL5e, PCL6, PS3, PDF 1.4, TIFF
Duplex	Standard
<b>Copy</b>	
Speed	Up to 33 cpm in A4 (35 cpm in Letter)
Resolution	Up to 1200 x 1200 dpi effective output
First Copy Out Time (Mono)	Less than 9.5 seconds (From Ready mode)
Zoom Rate	25~400% (platen), 25~100% (ADF)
Multy Copy	1~99 pages
Duplex Copy	Standard (1:1,1:2)
<b>Scan</b>	
Compatibility	TWAIN Standard, WIA Standard
Method	Color CCD
Resolution (Optical)	Up to 600 x 600 dpi
Resolution (Enhanced)	Up to 4,800 x 4,800 dpi
Scan to	PC, Email, USB Memory, FTP, SMB
<b>FAX</b>	
Compatibility	ITU-T G3
Modem Speed	33.6Kbps
Resolution	Standard : 203 x 98 dpi Fine/Photo : 203 x 196 dpi Super Fine : 300 x 300 dpi Color: Up to 200 x 200 dpi
Memory	4Mb (225 pages)
Auto Dial	Speed dial : 200 Locations
Fax Feature	On hook Dial, Auto Redial, Last Number Redial, Auto Reduction, Multi-send, Delayed Send, Fax forwarding (Email/Fax), Broadcasting up to 209 locations
<b>Paper Handling</b>	
Input Capacity and Types	250-sheet Cassette Tray, 50-sheet Multi-purpose Tray, 250 sheet Optional Cassette
Output Capacity and Types	150-sheet Face Down, 1-sheet Face Up
Media Size	76.2 x 127 mm (3" x 5") ~ 215.9 x 355.6 mm (8.5" x 14")
Media Type	Plain paper, transparency, envelope, labels, card stock, thick, thin, cotton, color, preprinted,recycled, bond, archive
ADF Capacity	50-sheet
ADF Document Size	Width: 142 ~ 216 mm (5.6" ~ 8.5") Length: 148 ~ 356 mm (5.8" ~ 14")
<b>General</b>	
LCD	4 line Graphic LCD
Memory / Storage	128 MB (Max. 384 MB)
OS Compatibility	Windows 2000/2003/2008 Server/XP/Vista, Various Linux OS, Mac OS X 10.3~10.5, Windows Terminal Services, Citrix Presentation Server (Compatible), SAP (Compatible)
Interface	Hi-Speed USB 2.0, Ethernet 10/100 BaseTX
Noise Level	Less than 52 dBA (Printing), Less than 52.5 dBA (Copying), Less than 26dB (Initial Standby)
Duty Cycle, Monthly	80,000 pages
Dimension (W x D x H)	466 x 435 x 458 mm
Weight	18.8 kg
<b>Consumables</b>	
Type	Single Cartridge
Yield	Standard: Average Cartridge Yield 4,000 standard pages. High Yield: Average cartridge Yield 10,000 standard pages. (Ships with 4,000 pages Starter Toner Cartridge) Declared cartridge yield in accordance with ISO/IEC 19752
Model Code	MLT-D208S, MLT-D208L (MLT-D2082S, MLT-D2082L for EU)
<b>Options</b>	
Options	Memory : 128MB(CLP-MEM201), 128MB(CLP-MEM202) Paper Cassette : 1EA x 250-sheet (SCX-S5635A) Wireless Lan(ML-NWA30L)

Distributed by

Printing solutions  
as easy as

