

# MX-M200D SPECIFICATIONS

## Main Specifications

Type:	Digital duplex copier-based MFP, desktop
Copy System:	Dry electrostatic transfer system
Originals:	Sheets, bound documents
Original Size:	11" x 17" maximum
Copy Size: Min.	5 1/2" x 8 1/2", Max. 11" x 17"
Copy Speed:	20 copies per minute (8 1/2" x 11"), 15 copies per minute (8 1/2" x 11" R), 12 copies per minute (8 1/2" x 14"), and 10 copies per minute (11" x 17")
Continuous Copy:	Max. 999 copies
First Copy Time:	7.2 Seconds or less (letter-size original, full ready condition) <sup>1</sup>
Warm Up Time:	45 Seconds or less <sup>1</sup>
Zoom Range:	25% to 400% in 1% increments (with SPF/R-SPF 50-200%)
Fixed Zoom Mode:	50%, 64%, 77%, 95%, 100%, 121%, 140%, 200%
Paper Feed System:	Standard: 2 x 250-sheet tray, and 100-sheet Bypass Tray. Optional: 1 x 250-sheet paper tray (AR-D34) or 2 x 250-sheet paper tray (AR-D35)
Original Feed System:	Standard: 40-sheet reversing single pass document feeder
Paper Type:	Paper Cassettes: 15-24 lb. standard or recycled bond paper Bypass Tray: Up to 100 sheets 15-20 lb. standard bond or recycled bond paper, up to 30 sheets for (multi-sheet feed): postcards, up to 5 sheets for envelopes (#10 monarch) (Single-sheet feed): 15-55 lb. standard or recycled bond paper, OHP, labels, and envelopes
Copy Resolution:	Scan: 600 dpi/Output: 600 dpi
Copy Features:	Electronic Sorting, Scan-Once-Print-Many, Auto Paper Sensing (APS), Auto Magnification Sensing (AMS), auto tray switching, manual zoom, card shot
Memory:	48 MB (standard), 256 MB memory expansion (optional)
Output Tray Capacity:	250 sheets (face down)
Fusing System:	Heat roller
Developer System:	Dry-type Dual component Magnetic Brush Development
Power Requirement:	AC 120 V, 60 HZ, 12 Amps
Power Consumption:	Max 1.2kW
Weight:	Approx. 84 1/2 lbs.
Dimensions:	Approx. 23 3/4" (w) x 22 3/4" (d) x 25 3/4" (h)

## Printer Function (Standard)

PDL:	Standard host-based JBIG printing, optional PCL <sup>®</sup> 6 and PS3
Print Speed:	20 ppm
Resolution:	600 dpi
Operating System:	Windows <sup>®</sup> 2000, Windows XP, Windows Vista <sup>™</sup>
Interface:	USB 2.0
Printer & Scanner Drivers and Utilities:	SPLC: Integrated Installer, SPLC Driver, Color Scan (TWAIN (USB)), Button Manager, Sharpdesk, PC-Fax Driver

## Scanner Function (Standard)

Scan Modes:	Color, monochrome, grayscale <sup>2</sup>
Scan Resolution:	Up to 600 x 600 dpi <sup>2</sup>
Scanning Method:	Document glass/document feeder
Scan Levels:	256 levels
Protocol:	TWAIN

<sup>1</sup> May vary depending on product configuration, machine settings and operating and/or environmental conditions.

<sup>2</sup> Some features require 256 MB memory expansion.

<sup>3</sup> Based on ITU Test chart#1 in standard resolution, actual transmission time will vary based on line conditions.

## PCL6 Network Printing/Network Scanning Expansion Kit (Optional)

Features:	PCL6 network printing and network scanning with web-based management function
Standard Memory:	64 MB standard, expandable to 320 with optional 256 MB DIMM
Operation Systems:	Windows 2000, Windows XP, Mac OS 8.6-9.2.2, 10.2.8, 10.3.9, 10.4.11 and 10.5-10.5.06
Network Protocols:	TCP/IP, IPX/SPX (Netware), NetBEUI and Ether Talk/AppleTalk
Interface:	RJ45 Ethernet; 10/100baseT
Utilities:	Web-based management, NIC Manager, Integrated Software Installer, Printer Administration Utility (PAU), Printer Status Monitor
Print Emulation:	PCL6/PCL5e Optional PS3
Print Resolution:	600 dpi
Scanning Resolution:	Up to 600 dpi (color/monochrome/grayscale) <sup>2</sup>
Operating Systems for Scanning:	Windows 2000, XP, Vista
Scanning Features:	Scan to E-mail, scan to desktop, scan to FTP, scan to URL and scan to print
Scanning Formats:	TIFF, PDF, JPEG
Scanning Software:	Sharpdesk document management software

## Super G3 Fax Kit (Optional)

Transmission Mode:	Super G3, G3
Modem Speed:	33.6 Kbps
Compression Methods:	JBIG, MMR, MR, MH
Scanning Method:	Sheet fed
TX Resolution:	400 dpi (ultra-fine)
Transmission Speed:	Approx. 2 seconds with JBIG <sup>3</sup>
Auto-Dialing Methods:	350 auto/group dialing destinations
Group Dialing:	Up to 50 destinations
Broadcasting:	Up to 200 destinations
Programs:	9 profiles
Memory:	2 MB standard/10 MB max. (8 MB option)
Halftone:	256 levels

## Optional Equipment

AR-55ABDH:	Deluxe High Cabinet
AR-55ABDL:	Deluxe Low Cabinet
AR-D34:	250-sheet paper feed unit (single cassette)
AR-D35:	500-sheet paper feed unit (dual 250-sheet cassettes)
AR-D5133NT:	Digital Power Filter
MX-NB10:	Network Expansion Kit
MX-TR10:	Job Separator
MX-PK10:	Postscript <sup>®</sup> 3 <sup>™</sup> Kit
MX-FX10:	Fax Expansion Kit
AR-MM9:	Fax Memory Kit
SHP32X64S133C3-B:	256 MB MFP Memory Expansion
SHP32X64S133SC3-B:	256 MB MX-NB10 Memory Expansion

## Supplies

MX-206NT:	Toner Cartridge
AR-205MD:	Developer
AR-205DR:	Drum



SHARP ELECTRONICS CORPORATION  
Sharp Plaza, Mahwah, NJ 07495-1163  
1-800-BE-SHARP • www.sharppusa.com



Design and Specifications subject to change without notice. Sharp, Sharp OSA, Sharpdesk, My Sharp and all related trademarks are trademarks or registered trademarks of Sharp Corporation and/or its affiliated companies. Windows, Windows NT, Windows Server and Windows Vista are trademarks or registered trademarks of Microsoft Corporation. All other trademarks are the property of their respective owners.